



## USG Ensemble™ Acoustical Drywall Ceiling United States Gypsum Company

**Final Assembly:** Walworth, WI

**Life Expectancy:** 30+ Year(s)

**End of Life Options:** Salvageable/Reusable in its Entirety, Landfill (100%)

### Ingredients:

**USG Sheetrock® Brand Ensemble™ Panels:** Calcium sulfate dihydrate; Cellulose; Mineral wool; Starch; Adhesive; Aluminum hydroxide; Proprietary (0.05-0.2%)<sup>1</sup>; Dextrose; Metaphosphoric acid (H<sub>3</sub>P<sub>3</sub>O<sub>9</sub>), trisodium salt; **USG Ensemble™ Spray-Applied Finish:** Water; Calcium Carbonate; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Mineral wool; Titanium dioxide; Calcined kaolin; Proprietary (0.17-0.34%)<sup>1</sup>; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; 1,3,5-Triazine-1,3,5(2H,4H,6H)-triethanol; **USG Ensemble™ High-NRC Backer Panels:** Mineral wool fiber; Styrene-based polymer; Starch; Stucco; **USG Fiberock® Brand End-joint Backer Panel:** Calcium sulfate dihydrate; Cellulose; **USG Sheetrock® Brand Ensemble™ Ceiling Compound:** Water; Calcium Carbonate; Adhesive; Attapulgit; Proprietary (0.02-0.04%)<sup>1</sup>; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; 1,3,5-Triazine-1,3,5(2H,4H,6H)-triethanol; **Fasteners:** Steel; **USG Sheetrock® Brand Paper Joint Tape:** Cellulose

<sup>1</sup>LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- |   |                               |
|---|-------------------------------|
| <input type="checkbox"/> LBC Red List Free                | % Disclosed: 99.42% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: 12.8 g/L         |
| <input type="checkbox"/> Declared                         |                               |

**I-10 Interior Performance:** CDPH Standard Method v1.2-2017

**I-14 Responsible Sourcing:** Not Applicable

USG-0048  
EXP. 01 SEP 2021  
Original Issue Date: 2018